

Launching soon

# Compact flight type dishwasher

Optimizing performance with compact design

## Characteristics and advantages

- **High productivity:** Up to 3800-5200 dishes/h
- **Water and energy savings:** 15% less water and 17% less energy
- **Guaranteed hygiene:** Precise thermal control of rinse water temperature
- **Built-in pressure reducer:** Stable rinse water pressure during the rinse phase
- **Easy to use:** Panel with temperature display
- **Easy to service and maintain:** Electrical control box and main components on top and front
- **Quick on-site installation:** Using preset external chemical connection terminal
- **Avoid injury risk:** Washing will stop when door is open
- **Safety first:** Designed to prevent dry heating failure at low water levels
- **Better drying:** Optimized design to improve drying result

External dimension (W*D*H mm)	2950*857*1692
Loading direction	L>R or R>L
Electric supply	380V/50Hz/3N
Installed power (kW)	45
Max productivity (dishes/h)	3800-5200
Clearance (mm)	412*612
Wash temperature (°C)	55-60
Rinse temperature (°C)	82-90
Rinse water consumption (l/h)	350
Inlet water pressure (bar)	2-5
Inlet water temperature (°C)	10-60
Inlet pipe size (inch)	G 3/4"
Drain pipe size (inch/mm)	2"
Dryer (optional)	10kw, 800*857*1980mm