

Compact flight type dishwasher

Optimizing performance with compact design

Characteristics and advantages

- **High productivity:** Up to 3800 dishes/h
- **Water and energy savings:** 15% less water and 17% less energy with insulation door
- **Guaranteed hygiene:** Precise thermal control of rinse water temperature
- **Built-in pressure reducer:** Stable rinse water pressure during the rinse phase
- **Easy to use:** Panel with temperature display
- **Easy to service and maintain:** Electrical control box and main components on top and front
- **Quick on-site installation:** Using preset external chemical connection terminal
- **Avoid injury risk:** Washing will stop when door is open
- **Safety first:** Designed to prevent dry heating failure at low water levels
- **Better drying:** Optimized design to improve drying result by 30%



PNC	521007	521008
Model	FTS-LD	FTS-RD
External dimension (W*D*H mm)	3750*876*1978	
Loading direction	L>R	R>L
Electric supply	380V/50Hz/3N	
Installed power (kW)	55	55
Max productivity (dishes/h)	3800	
Clearance (mm)	412*612	
Wash temperature (°C)	55-60	
Rinse temperature (°C)	82-90	
Rinse water consumption (l/h)	350	
Inlet water pressure (bar)	2-5	
Inlet water temperature (°C)	10-60	
Inlet pipe size (inch)	G 3/4"	
Drain pipe size (inch/mm)	2" or 50mm	
800mm Dryer(kW)	9.55	